

### 850nm, Red Laser Module



#### Application

Industrial areas / Medical / Biochemical / Laser Tag

#### Property

Wavelength Range = 850nm (others optional)


#### Introduction

Egismos created compact laser series that have very attractive price tag. Our standard modules are emitting 780nm and 850nm wavelengths, however custom wavelength are also available. Other characteristics like TTL or custom optics is also available upon a customer's request.

### Specifications (T=25°C)

Items	Symbols	S638501D S638505D
Mode		CW
Wavelength	$\lambda$	850nm
Lens		PMMA
Spot	D/R	Dot
Spot Size		<15x30mm at 10m
Diameter x Length	$\Phi \times L$	6x10.5mm (without PCB)
Output Power	$P_o$	<1mW, <5mW
Power Stability		<10%
Divergence Angle	mrad	<1
Operating Voltage(DC)	$V_o$	3V
CW Operating Current	$I_o$	25~30mA, 30mA max
Operating Temperature	$T_o$	-10°C ~ +50°C
Storage Temperature	$T_s$	-40°C ~ +80°C
Housing Material		Brass
Mean time to failure		>5000 hrs

### Outline Dimensions



### Spot size Define

S6 Series Dot Shape at 10m



### Spot size

The spot size defined as Gaussian beam. In optics, a Gaussian beam is a beam of electromagnetic radiation whose transverse electric field and intensity (irradiance) distributions are well approximated by Gaussian functions. Many lasers emit beams that approximate a Gaussian profile, in which case the laser is said to be operating on the fundamental transverse mode, or "TEM00 mode" of the laser's optical resonator. When refracted by a diffraction-limited lens, a Gaussian beam is transformed into another Gaussian beam (characterized by a different set of parameters), which explains why it is a convenient, widespread model in laser optics.

### Power Stability

The actual output power will be between the range 2.5mW to 3.5mW, but once made sure the value, for example,  $3\text{mW} \pm 0.15\text{mW}$  or  $3.2\text{mW} \pm 0.16\text{mW}$  in the 25 °C temperature. Then the power stability represents 5%.

### Mean time to failure(MTTF)

Mean time to failure (MTTF) is the length of time a device or other product is expected to last in operation. MTTF is one of many ways to evaluate the reliability of pieces of hardware or other technology. It's important to note, however, that the mean time to failure metrics provided by companies regarding specific products or components may not have been collected by running one unit continuously until failure. Instead, MTTF data is often collected by running many units, even many thousands of units, for a specific number of hours.



## Laser Safety

The light emitted from these devices has been set in accordance with IEC60825. However, staring into the beam, whether directly or indirectly, must be avoided.

### Class I

The maximum permissible exposure(MPE) cannot be exceeded, it includes High-power lasers within an enclosure that prevents exposure to the radiation and that cannot be opened without shutting down the laser. For example, a continuous laser at 600nm can emit up to 0.39mW, but for shorter wavelengths, the maximum emission is lower.

### Class II

"Caution", visible laser light less than 1.0mW. Considered eye safe, normal exposure to this type of beam will not cause permanent damage to the retina.

### Class IIIA

"Danger", visible laser light between 1.0mW and 5.0mW. Considered eye safe with caution. Focusing of this light into the eye could cause some damage.

### Class IIIB

"Danger", infrared(IR), and high power visible lasers considered dangerous to the retina if exposed. NB: it is important to note that while complying with the above classifications, unless otherwise stated. Our laser diode products are not certified and are designed solely for use in OEM products. The way in which device is used in the final product may alter its original design classification, and it is the responsibility of the OEM to ensure compliance with the relevant standards.