

### 515nm, Green Laser Module



#### Application

Industrial areas / Medical / Biochemical / Gun Sight

#### Property

Wavelength Range = 515nm (others optional)


#### Introduction

Egismos created high stability and quality laser modules that are successfully applied in aerospace, military industry, biochemistry, medicine etc.

### Specifications (T=25°C)


Items	Symbols	H435151D/R H435155D/R
Mode		Pulse Width Modulation (PWM)
Wavelength	$\lambda$	515nm
Lens		Glass
Spot	D/R	Dot/Round
Spot Size	D	<10x14mm at 10m
	R	< $\Phi$ 5mm at 3m
Diameter x Length		4.5x10mm(without PCB)
Output Power	Po	<1mW, <5mW
Power Stability		<5%
Divergence Angle	mrad	<0.7
Operating Voltage (DC)	Vo	2.7V / 5V
CW Operating Current	Io	110mA, max (depends on driving voltage)
Operating Temperature	To	-10°C ~ +60°C
Storage Temperature	Ts	-40°C ~ +85°C
Housing Material		Aluminum
Mean time to failure		>8000 hrs

### Outline Dimensions




### Spot size Define

H4 series Dot Shape at 10m



H4 series Round Shape at 3m



### Spot size

The spot size defined as Gaussian beam. In optics, a Gaussian beam is a beam of electromagnetic radiation whose transverse electric field and intensity (irradiance) distributions are well approximated by Gaussian functions. Many lasers emit beams that approximate a Gaussian profile, in which case the laser is said to be operating on the fundamental transverse mode, or "TEM00 mode" of the laser's optical resonator. When refracted by a diffraction-limited lens, a Gaussian beam is transformed into another Gaussian beam (characterized by a different set of parameters), which explains why it is a convenient, widespread model in laser optics.

### Power Stability

The actual output power will be between the range 2.5mW to 3.5mW, but once made sure the value, for example,  $3\text{mW} \pm 0.15\text{mW}$  or  $3.2\text{mW} \pm 0.16\text{mW}$  in the 25 °C temperature. Then the power stability represents 5%.

### Mean time to failure(MTTF)

Mean time to failure (MTTF) is the length of time a device or other product is expected to last in operation. MTTF is one of many ways to evaluate the reliability of pieces of hardware or other technology. It's important to note, however, that the mean time to failure metrics provided by companies regarding specific products or components may not have been collected by running one unit continuously until failure. Instead, MTTF data is often collected by running many units, even many thousands of units, for a specific number of hours.



## Laser Safety

The light emitted from these devices has been set in accordance with IEC60825. However, staring into the beam, whether directly or indirectly, must be avoided.

### Class I

The maximum permissible exposure(MPE) cannot be exceeded, it includes High-power lasers within an enclosure that prevents exposure to the radiation and that cannot be opened without shutting down the laser. For example, a continuous laser at 600nm can emit up to 0.39mW, but for shorter wavelengths, the maximum emission is lower.

### Class II

"Caution", visible laser light less than 1.0mW. Considered eye safe, normal exposure to this type of beam will not cause permanent damage to the retina.

### Class IIIA

"Danger", visible laser light between 1.0mW and 5.0mW. Considered eye safe with caution. Focusing of this light into the eye could cause some damage.

### Class IIIB

"Danger", infrared(IR), and high power visible lasers considered dangerous to the retina if exposed. NB: it is important to note that while complying with the above classifications, unless otherwise stated. Our laser diode products are not certified and are designed solely for use in OEM products. The way in which device is used in the final product may alter its original design classification, and it is the responsibility of the OEM to ensure compliance with the relevant standards.